

2.5" to 3.5" SSD & SATA HDD Converter Box For Internal & External Use



USER'S MANUAL HDCV-1





Specficiations:

 2.5" to 3.5" SSD & SATA HDD Converter Box For Internal & External Use

Interface: Standard SATA

Dimensions: 5 3/4" (L) x 4" (W) x 15/16"

• Weight: 0.4 LBS

Supports: 1.5G/3.0G Speed for SATA

Supports: SATAII NCQ

Transfer rate of Hi-Speed USB Approx. 480mbps

 Support OS: Win 2000/ME/XP/Vista/7 Mac OS 10X or Higher

Features:

- Internal Use: Converts 2.5" to 3.5" SATA H.D.D.
- External Use: 2.5" SATA HDD Enclosure with USB 2.0
- HDD Eject Button
- Red LED light for Power On/Off and HDD activity
- Hot Plug and Play
- RoHS Compliant

Accessories

Package Contents

	5, 5, 51, 11, 1
HDCV-1	1pcs
SATA Data Cable	1pcs
USB Cable	1pcs
Manual	1pcs

Quantity

Components:



- 1. Insert 2.5" SSD or SATA HDD
- 2. Converts 2.5" HDD to 3.5" HDD



- 1. HDD Eject Button
- 2. Red LED light for Power On/Off and HDD activity



- 1. Internal Use: Converts 2.5" to 3.5" SATA H.D.D.
- 2. External Use: 2.5" SATA HDD Enclosure w/ USB 2.0
- 3. SATA Power 15Pin+ SATA Data 7Pin connector
- 4. Mini USB Connector

Installation:

Internal Use:



- 1. Insert 2.5" SSD or SATA H.D.D. into HDCV-1
- 2. Converter to 3.5" SATA HDD can install in case
- 3. Converter to 3.5" SATA HDD can insert into Internal Mobile Rack Tray

External Use:



After inserting the 2.5" SSD or SATA H.D.D. into HDCV-1 it can be used for externally, as an external enclosure.



- 1) After inserting HDD, carefully push until it is seated into position, excessive force may damage its mechanical parts.
- 2) If the HDD is inserted backward into the tray, forcing the device may damage the HDVC-01

Removal:

Eject HDD from the HDCV-1

- 1. Do not eject HDD while it is running
- 2. Carefully eject HDD out from HDCV-1, the HDD can reach temperatures over 50C, it will not burn the finger but should be handled with care





Kingwin is not responsible for any data loss or HDD damage in the process of using the HDVC-1



HDCV-1

2.5" to 3.5" SSD & SATA HDD Converter Box For Internal & External Use



KWI Technology Inc. - U.S.A. (Headquarters)

4020 Valley Blvd, Unit 100

Walnut, CA 91789

TEL: 1-909-598-2888 FAX: 1-909-348-1133

E-MAIL: info@kingwin.com Website: www.kingwin.com